

1

**SYSTEM AND METHOD FOR  
INDEPENDENT POWER SEQUENCING OF INTEGRATED CIRCUITS**

5

**ABSTRACT OF THE DISCLOSURE**

A circuit for applying power to mixed mode integrated circuits in a predefined sequence. The circuit includes a first circuit powered by a first voltage and a second circuit powered  
10 by a second voltage that is less than the first voltage and having the second voltage coupled to the first circuit. The circuit for applying power to mixed mode integrated circuits includes, a modified IO cell of the second circuit. The modified IO cell has a driver transistor including a back gate terminal,  
15 a gate terminal that is driven by the second circuit, a source terminal that is coupled to a first circuit signal, and a drain terminal that is coupled to the second power supply. The circuit for applying power to mixed mode integrated circuits further includes, a controller circuit coupled to the first voltage and  
20 the second voltage supplied as controller circuit inputs. The controller circuit has a plurality of controller circuit outputs. The circuit for applying power to mixed mode integrated circuits also includes, a back gate bias application circuit. The back gate bias application circuit has a plurality of inputs coupled  
25 to the plurality of controller circuit outputs, and an output coupled to the backgate of the driver transistor backgate terminal.

LLW PAS258833.2--6/29/00 3:14 PM

30

35